

01-18-00

Patent Offices
Jason Z. Lin, Ph.D.
REGISTERED PATENT AGENT
19597 Via Monte Drive
Saratoga, CA 95070

TEL. (408) 867-9757
FAX (408) 867-7437

January 14, 2000

Agent's Docket No. UPA-00103

Assistant Commissioner for Patents
Washington, D.C. 20231

Re: **U.S. Utility Patent Application**
Inventor: **Dai-Liang Ting, Lisen Chuang and Ching-Chao Chang**
Title: **Electrode Structure For A Wide Viewing Angle Liquid Crystal Display**

Sir:

The above-identified utility patent application is transmitted herewith for filing:

Enclosed are:

1. **Ten (10)** sheets of specification, claims, and abstract.
2. **Four (4)** sheets of drawings containing FIGs. 1 through 4.
3. An executed Declaration and Power of Attorney for Utility Patent Application.
4. A certified copy of Taiwan Patent Application No. 088108187A01 filed September 13, 1999.
5. A Recordation Form Cover Sheet and an Assignment which the Commissioner is requested to record and return to the undersigned.
6. A Check in the amount of **\$730.00** to cover following government fees:
 - a) Basic utility patent filing: **\$690.00** (one independent claim and eight dependent claims).

Certificate of Mailing

I hereby certify that this correspondence is being deposited with the United States Postal Service with sufficient postage as Express Mail in an envelope addressed to: Box New Application, Assistant Commissioner for Patents, Washington, D.C. 20231, on the date shown below.

Date. Jan. 14, 2000

Mail Label


By. Jason Z. Lin

EL410149118US

b) Assignment recordation fee: **\$40.00.**

Please kindly acknowledge receipt of the above items by having your mailroom stamp and return the enclosed postcard.

Respectfully submitted,



Jason Z. Lin
Agent for Applicant
Reg. No. 37,492

004410 37492

ELECTRODE STRUCTURE FOR A WIDE VIEWING ANGLE LIQUID CRYSTAL DISPLAY

FIELD OF THE INVENTION

The present invention relates generally to an electrode structure of a liquid
5 crystal display, and more particularly to an electrode structure of a wide viewing
angle liquid crystal display.

BACKGROUND OF THE INVENTION

A large number of liquid crystal display (LCD) panels have recently been
employed as display devices in electronic products. The technologies of wide
10 viewing angle liquid crystal displays have been disclosed very often in recent years.
In a Taiwan patent application No. 88108187 entitled "Electrode Structure of A
Wide Viewing Angle Liquid Crystal Display", an electrode structure for providing
wide viewing angle is disclosed. The electrode structure comprises an upper
electrode layer having multiple comb-shaped and parallel conductors on a glass
15 substrate, a lower electrode layer having a TN-type conductor and a layer of non-
conductive insulator formed between the upper and lower electrode layers.

In the embodiment of the Taiwan patent application, the pixel electrodes in
the upper layer of the electrode structure has a comb-shaped structure while the
common electrode in the lower layer has a plate-shaped structure. A layer of
20 negative-type liquid crystal is used to fill the space between the upper and lower
glass substrates of the LCD. The two electrode layers are fabricated on the lower
glass substrate.

The drawback of the electrode structure disclosed in the Taiwan patent application is that the liquid crystal driven by an electric voltage rotates toward one direction. Therefore, the effect of color dispersion at different viewing angle limits the viewing angle of the LCD and degrades the quality of the display.

5 SUMMARY OF THE INVENTION

The present invention has been made to overcome the above-mentioned drawback of the electrode structure in the prior art. The primary object of the invention is to provide an electrode structure for a wide viewing angle liquid crystal display. The electrode structure has upper and lower electrode layers. The pixel
10 electrode in the upper layer has a herringbone-shaped structure while the common electrode in the lower layer has a plate-shaped structure.

The liquid crystal display has two separated glass substrates between which liquid crystals are filled. Multiple scan signal lines, multiple data signal lines, multiple switching elements, and a layer of common electrodes are fabricated on the
15 surface of the lower glass substrate. The scan signal lines are perpendicular to the data signal lines in order to form a pixel matrix. A passivation layer made of a transparent non-conductive insulator is formed between the layer of pixel electrodes and the layer of common electrodes.

The herringbone-shaped structure of the pixel electrodes allows the liquid
20 crystal molecules to rotate in two directions, clockwise and counterclockwise. The color dispersion caused by a wide viewing angle is thus compensated for. The herringbone-shaped structure also helps to maintain the brightness of pixels.

The foregoing and other objects, features, aspects and advantages of the present invention will become better understood from a careful reading of a detailed description provided herein below with appropriate reference to the accompanying drawings.

5 BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a top view showing the electrode structure of a single pixel for a wide viewing angle liquid crystal display according to the preferred embodiment of the present invention.

FIG. 2 shows the liquid crystal rotates in two opposite directions according to the
10 electrode structure of the present invention.

FIG. 3 shows the cross section along line AA' and line BB' of FIG. 1.

FIG. 4 illustrates the brightness distribution in a single pixel of the electrode structure of the present invention when an electric voltage is applied.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

15 FIG. 1 is a top view showing the electrode structure 100 of a single pixel for a wide viewing angle liquid crystal display according to the preferred embodiment of the present invention. Referring to FIG. 1, the upper layer of the electrode structure 100 comprises a plurality of pixel electrodes 101 each having a herringbone-shaped structure while the lower layer comprises a common electrode
20 102 having a plate-shaped structure. The scan signal line region 103 is perpendicular to the data signal line region 104 to form a pixel.

As shown in FIG. 1, a thin film transistor 105 used as a switching device is located near the crossing point of the scan signal line region 103 and the data signal line region 104 in a single pixel. The scan signal line region 103 and the data signal line region 104 are adjacent to the area where the pixel electrodes 101 are formed.

5 The thin film transistor is an active switching device that controls the charging and discharging of the pixel electrodes. In addition to the thin film transistor, the active switching device may also be a Metal Oxide Semiconductor (MOS) transistor, a diode, a Metal-Insulator-Metal (MIM) transistor or a variable resistor according to the invention.

10 The following illustrates in detail the electrode structure of a wide viewing angle liquid crystal display of the present invention. The electrode structure including a common electrode layer, a pixel electrode layer, and a passivation layer is formed above a glass substrate. On the top surface of the glass substrate, there are multiple scan signal lines, multiple data signal lines, multiple switching elements,
15 and a layer of common electrodes. The passivation layer is made of a transparent non-conductive insulator and located between the common electrode layer and the pixel electrode layer. The passivation layer can be formed by depositing or growing an insulator film on the thin film transistor.

For every single pixel, the data signal line is located above and perpendicular
20 to the scan signal line. At least a switching element such as a thin film transistor 105 is fabricated near the crossing point of the scan signal line and the data signal line. The gate terminal of the switching element connects to the scan signal line, the drain terminal connects to the data signal line and the source terminal connects to the pixel

electrode.

As mentioned above, the pixel electrode has a herringbone-shaped structure. Pixel electrodes are formed in parallel. The turning angle θ shown in FIG. 2 in the herringbone-shaped structure is within a pre-defined range, about 45 to 90 degrees.

5 The herringbone-shaped structure of the pixel electrodes allows the liquid crystal molecules 201 to rotate in two directions, clockwise and counterclockwise. As shown in FIG. 2, the liquid crystal molecules 201 rotates in both clockwise and counterclockwise directions by a θ angle. The color dispersion caused by a viewing angle is thus compensated for and the effect of color dispersion is reduced.

10 The herringbone-shaped structure of the pixel electrodes maintains the brightness above the pixel electrodes in the certain range of θ . The intensity is proportional to the square of $\sin 2\theta$, therefore, if the turning angle θ is less than 45 degrees, the maximal value of θ is also less than 45 degrees. The pixel brightness will not reach its maximum value.

15 According to the invention, the electrode pitch in the layer of pixel electrodes is about 1 to 15 μm and the electrode width is about 1 to 10 μm . In the structure of a single pixel, the herringbone-shaped pixel electrodes 101 and the common electrode 102 both keep a distance from the scan signal line region 103 and the data signal line region 104. They do not cross over the scan signal line region 103 and the data signal
20 line region 104.

FIG. 3 shows the cross section along line AA' and line BB' of FIG. 1. Along line AA' of FIG. 1 is the steps of fabricating the thin film transistor, the data line and

the scan line. Along line BB' is the steps of fabricating the pixel electrodes 101 and the common electrode 102.

Referring to FIG. 3, the cross section along line AA' of FIG. 1 illustrates in detail every layer of the structure above the substrate. A metallic layer of the scan
5 signal line 301 is first formed above the glass substrate 303. Then, the glass substrate 303 is covered with an insulator layer 304 and an island-like region 305 is formed to provide an active layer for the thin film transistor. The thin film transistor comprises at least a gate, a drain, and a source. The gate terminal of the thin film transistor connects to the scan signal line 301, the drain terminal connects to the data
10 signal line 307 and the source terminal connects to the pixel electrodes 306.

The present invention forms a layer of plate-shaped common electrodes 306. The plate-shaped common electrodes 306 can be made of transparent or non-transparent conductive materials. The general transparent conductive materials may be indium-tin-oxide (ITO), SnO_2 , N type amorphous silicon film, N type poly-
15 silicon film, P type poly-silicon film, and ZnO, etc. Non-transparent conductive material may be other metallic material. The plate-shaped common electrodes 306 do not cross over the island-like region 305, as shown in FIG. 3.

Above the island-like region 305 is a metallic layer of data signal lines 307. A passivation layer 308 is further used to cover the substrate. Similarly, the electric
20 contact with the data signal line metallic layer 307 can be established by forming multiple contact holes outside the pixel region.

Along line BB' of FIG. 1 is the steps of forming the layer of pixel electrodes

and the common electrodes. A layer of herringbone-shaped pixel electrodes 309 is fabricated above the layer of common electrodes 306 and the passivation layer 308. The herringbone-shaped pixel electrodes 309 can be made of transparent or non-transparent conductive materials.

5 As mentioned above, the structure of the herringbone-shaped pixel electrodes preserves the brightness of pixels. FIG. 4 illustrates the distribution of brightness in a single pixel of the electrode structure of the present invention when an electric voltage is applied. The brightness at the middle portion 401 of the herringbone-shaped pixel electrode is almost zero. However, more than 70%
10 effective transmission of light can be achieved at regions 402, 403, 404, and 405 that are parallel to each other.

 Although this invention has been described with a certain degree of particularity, it is to be understood that the present disclosure has been made by way of preferred embodiments only and that numerous changes in the detailed structure
15 and combination as well as arrangement of parts may be restored to without departing from the spirit and scope of the invention as hereinafter set forth.

What is claimed is:

- 1 1. An electrode structure of a wide viewing angle liquid crystal display
2 comprising:
3 a scan signal line;
4 a data signal line perpendicular to said scan signal line, said scan signal line and
5 said data signal line defining a pixel area;
6 a common electrode in said pixel area;
7 a passivation layer above said common electrode; and
8 a plurality of pixel electrodes each having a herringbone-shaped structure and
9 running substantially in parallel with said data signal line above said passivation
10 layer and said common electrode.
- 1 2. The electrode structure of a wide viewing angle liquid crystal display as claimed
2 in claim 1, said common electrode having a plate shape.
- 1 3. The electrode structure of a wide viewing angle liquid crystal display as claimed
2 in claim 1, said herringbone-shaped structure having a turning angle ranging
3 from 45 degrees to 90 degrees.
- 1 4. The electrode structure of a wide viewing angle liquid crystal display as claimed
2 in claim 1, said plurality of pixel electrodes having a pitch ranging from 1 to 15
3 μm and the width of each pixel electrode ranging from 1 to 10 μm .
- 1 5. The electrode structure of a wide viewing angle liquid crystal display as claimed
2 in claim 1, wherein said common electrode is made of indium-tin-oxide, SnO_2 ,
3 N-type amorphous silicon film, N type poly-silicon film, P type poly-silicon film,

4 or ZnO.

1 6. The electrode structure of a wide viewing angle liquid crystal display as claimed
 2 in claim 1, wherein said pixel electrodes are made of indium-tin-oxide, SnO_2 ,
 3 N-type amorphous silicon film, N type poly-silicon film, P type poly-silicon
 4 film, or ZnO.

1 7. The electrode structure of a wide viewing angle liquid crystal display as claimed
 2 in claim 1, wherein said pixel electrodes are made of metal material.

1 8. The electrode structure of a wide viewing angle liquid crystal display as claimed
 2 in claim 1, further comprising a switching device.

1 9. The electrode structure of a wide viewing angle liquid crystal display as claimed
 2 in claim 8, said switching device being a thin film transistor.

ABSTRACT

An electrode structure for a liquid crystal display includes a layer of pixel electrodes each having a herringbone-shaped structure, a passivation layer and a layer of common electrodes. The pixel electrodes are formed in parallel above the common electrodes. The herringbone-shaped structure of a pixel electrode has a predefined turning angle between 45 degrees to 90 degrees. The pixel electrode structure allows the liquid crystals in the display to rotate in two directions, clockwise and counterclockwise, to compensate for the color dispersion caused by a wide viewing angle.




FIG. 1




FIG. 2




FIG. 3




FIG. 4

**UNITED STATES OF AMERICA
COMBINED DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION**

**FILE NO.
UPA-00103**

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name and that I verily believe that I am the original, first and sole inventor(if only one name is listed below) or an original, first and joint inventor(if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled.

ELECTRODE STRUCTURE FOR A WIDE VIEWING ANGLE LIQUID CRYSTAL DISPLAY

the specification of which is attached hereto, unless the following box is checked:

☐ was filed on _____ as United States patent application Serial Number _____, or PCT International patent application No. _____ and was amended on _____ (if any).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose all information known to be material to patentability in accordance with Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119 of any foreign application(s) for patent or inventor's certificate or United States provisional application(s) listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s) or Provisional Application(s)

COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 35 U.S.C.119
Taiwan	088108187A01	September 13, 1999	YESX NO
			YES NO

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112 I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application

UNITED STATES APPLICATION NUMBER	DATE OF FILING (day, month, year)	STATUS (patented, pending, abandoned)

I hereby appoint Jason Z. Lin, Registration No. 37,492, whose address is list below, as my principal agent with full power of substitution and revocation to prosecute this application, to transact all business in the Patent and Trademark Office connected therewith and to receive all correspondence

SEND CORRESPONDENCE TO :

Jason Z. Lin
19597 Via Monte Drive Tel: (408) 867-9757
Saratoga, CA 95070 Fax: (408) 867-7437

I hereby declare that all statements made herein of my own knowledge are true and that all statement made on information and belief are believed to be true; and further that these statement were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon

FULL NAME OF SOLE OR FIRST INVENTOR Dai-Liang Ting	INVENTORS SIGNATURE <i>Dai-Liang Ting</i>	DATE Nov. 17, 1999
RESIDENCE 2F, 13-3, Alley 10, Lane 155, Sec. 2, Kuang-Fu Rd., Hsinchu, Taiwan, R.O.C.		COUNTRY OF CITIZENSHIP Taiwan, R.O.C.
POST OFFICE ADDRESS No. 195, Sec. 4, Chung Hsing Road, Chutung, Hsinchu, Taiwan 310, R.O.C.		
FULL NAME OF SECOND JOINT INVENTOR(if any) Lisen Chuang	INVENTORS SIGNATURE <i>Lisen Chuang</i>	DATE 1999 Nov. 17
RESIDENCE No. 122, Hushi Village, Hushi Country, Penghu, Taiwan, R.O.C.		COUNTRY OF CITIZENSHIP Taiwan, R.O.C.
POST OFFICE ADDRESS No. 195, Sec. 4, Chung Hsing Road, Chutung, Hsinchu, Taiwan 310, R.O.C.		
FULL NAME OF THIRD JOINT INVENTOR(if any) Ching-Chao Chang	INVENTORS SIGNATURE <i>Ching-Chao Chang</i>	DATE Nov. 17, 1999
RESIDENCE 3F, 9-1, Lane 16, Wenchou St., Taipei, Taiwan, R.O.C.		COUNTRY OF CITIZENSHIP Taiwan, R.O.C.
POST OFFICE ADDRESS No. 195, Sec. 4, Chung Hsing Road, Chutung, Hsinchu, Taiwan 310, R.O.C.		